

SPECIFICATIONS

| MODEL: | CJ-1 | FEATURES: |
|---|--|--|
| Style: | Direct drive | <ul style="list-style-type: none"> • 6,000 lb. maximum lifting capacity • Hot-dipped galvanized steel construction for durability • Galvanized platform • Durable individual 3 HP electrical gear reduction motor • Optional PLC system available for group operation • Accommodates cars, light trucks, motorcycles, and ATVs • Equalized drive shaft • Very quiet during operation • Manual release for lowering the car in case of power failure • Electrical motor can be 1 ph by special order • Electrical motor can be relocated to left side by special order |
| Maximum lifting Capacity: | 6,000 lb. (2,722 kg.) | |
| Overall Length: | 204-3/4" (5200mm) | |
| Overall Width: | 111-3/4" (2840mm) | |
| Overall Height: | 110-3/4" (2814mm) | |
| Lifting Height (Floor to bottom of platform): | 86-1/2" (2200mm) | |
| Width Between Posts: | 96" (2440mm) | |
| Platform Overall Width: | 91-1/4" (2320mm) | |
| Platform Parking Space Width: | 82-3/4" (2100mm) | |
| Platform Length: | 168-3/4" (4285mm) | |
| Min. Platform Height: | 4-21/64" (110mm) | SAFETY: <ul style="list-style-type: none"> • Safety locks at the top position • Electrical motor brake • Power controlled by a key to operate push up/down buttons |
| Lifting Time: | 50 Sec. | |
| Gear Reduction Motor: | 220 V, 60 Hz, 3 Ph - 3HP (1Ph optional) | |
| Weight: | 2,640 lb. (1,200kg) | |

